



DP5524 & DP3524

Dot Matrix Printer



- *High Performance*
- *Heavy Duty Print Head*

DP5524 & DP3524 Dot Matrix Printer



Technical Specifications

Description	DP5524		DP3524		
Printer Type	24-pin impact dot matrix				
Print Direction	Bi-directional Printing with logic seeking				
Printable columns	136 characters @10cpi				
Print Speed		10cpi	12cpi	10cpi	12cpi
	HSD	480 cps	-	400 cps	-
	Draft	360 cps	432 cps	300 cps	360 cps
	NLQ	240 cps	288 cps	200 cps	240 cps
	LQ	120 cps	144 cps	100 cps	120 cps
Print Language	ESC/P Emulation or customization				
Character Specifications	Character Sets	ASCII, Italic, PC437, PC850 etc 15 International Character sets			
	Fonts	Draft, Roman, Sans Serif etc			
		Bar Code Font	8 sets including EAN-13, Code 39, Code 128 etc		
Paper Handling	Width	Cut sheet	100~420mm		
		Continuous Paper	101~406mm		
	Thickness	0.065~0.52mm			
	Types	Cut Sheet, Continuous Paper, Multi-part Forms, Envelope, Post Card, Adhesive Labels			
	Paper Path	Friction Feed – rear in top out, front in top out			
Tractor Feed – rear in top out, front in top out, bottom in top out					
Copy Capability	Original + 5 copies		Original + 4 copies		
Interface	Parallel Interface; USB Interface (Optional); Serial Interface (Optional)		Parallel Interface; USB Interface (Optional); Serial Interface (Optional); LAN interface (Optional)		
Buffer	128KB				
Ribbon	Approx. 6 million characters				
Reliability	MTBF	20,000 hours	10,000 hours		
	Print Head Life	400 million strokes/wire	300 million strokes/wire		
Environment Condition	Operating Conditions	Temp: 5~35 C; Humidity: 20%~80%RH			
Electronics	Power Supply	Rated Voltage: 220VAC; Range: 165~264V AC			
	Frequency	49.5~60.5 Hz			
Dimension & Weight	Width x Length x Height	623 x 395 x 173mm			
	Weight	Approx. 11kg			
Certification & Standard (Base on the test of START model)	CCC: China Compulsory Certificate EMC: GB9254 Class B China Certificate for Energy Conservation Product				
Operating System	For Windows 95/98/2000/XP, VISTA, UNIX, LINUX etc				
Options	Network Print Server Ribbon Cartridge 2nd Tractor Unit				

Note : The Specification is subject to change without notice.

All product/brand names are trade marks or registered trademarks of their respective holders.